

## Safety Data Sheet

### Section 1: Identification

#### Product identifier

**Product Name** • G-501 Green Vinyl Ester Tooling Gel Coat

**Synonyms** • Tooling Gel Coat

#### Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** • Used in the manufacture of thermoset plastic parts

#### Details of the supplier of the safety data sheet

**Manufacturer** • Polycryl Corporation  
260 Pierce Road  
Oakland, TN 38060  
United States  
www.polycrylcorp.com  
rich@polycrylcorp.com

**Telephone (General)** • (901) 465-3330

#### Emergency telephone number

**Manufacturer** • (901) 483-5769

**Manufacturer** • 1-800-424-9300 - Chemtrec

### Section 2: Hazard Identification

#### United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

#### Classification of the substance or mixture

**OSHA HCS 2012** • Flammable Liquids 3  
Aspiration 1  
Skin Irritation 2  
Skin Sensitization 1B  
Eye Irritation 2  
Acute Toxicity Inhalation 4  
Respiratory Sensitization 1B  
Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation  
Carcinogenicity 2  
Reproductive Toxicity 2  
Specific Target Organ Toxicity Repeated Exposure 1

#### Label elements

**OSHA HCS 2012**

**DANGER**



- Hazard statements**
- Flammable liquid and vapour
  - May be fatal if swallowed and enters airways
  - Causes skin irritation
  - May cause an allergic skin reaction
  - Causes serious eye irritation
  - Harmful if inhaled
  - May cause allergy or asthma symptoms or breathing difficulties if inhaled
  - May cause respiratory irritation
  - Suspected of causing cancer.
  - Suspected of damaging fertility or the unborn child.
  - Causes damage to organs through prolonged or repeated exposure.

### Precautionary statements

- Prevention**
- Obtain special instructions before use.
  - Do not handle until all safety precautions have been read and understood.
  - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
  - Keep container tightly closed.
  - Ground and/or bond container and receiving equipment.
  - Use explosion-proof electrical/ventilating/lighting/equipment.
  - Use only non-sparking tools.
  - Take precautionary measures against static discharge.
  - Do not breathe mist, vapours and/or spray.
  - Wash thoroughly after handling.
  - Do not eat, drink or smoke when using this product.
  - Use only outdoors or in a well-ventilated area.
  - Contaminated work clothing should not be allowed out of the workplace.
  - Wear protective gloves/protective clothing/eye protection/face protection.
  - In case of inadequate ventilation wear respiratory protection.
- Response**
- In case of fire: Use appropriate media for extinction.
  - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
  - If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
  - Call a POISON CENTER or doctor/physician if you feel unwell.
  - If on skin: Wash with plenty of water .
  - Specific treatment, see supplemental first aid information.
  - Take off contaminated clothing and wash before reuse.
  - If skin irritation or rash occurs: Get medical advice/attention.
  - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
  - If eye irritation persists: Get medical advice/attention.
  - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
  - Do NOT induce vomiting.
  - IF exposed or concerned: Get medical advice/attention.
  - Get medical advice/attention if you feel unwell.
- Storage/Disposal**
- Store in a well-ventilated place. Keep container tightly closed.
  - Keep cool.
  - Store locked up.
  - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

- Supplemental information**
- 49-60 percent of this product consists of an ingredient of unknown toxicity.

### Other hazards

- OSHA HCS 2012**
- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

**Canada**

According to: WHMIS

**Classification of the substance or mixture**

WHMIS • Flammable Liquids - B2  
 Other Toxic Effects - D2A  
 Other Toxic Effects - D2B

**Label elements**

WHMIS



• Flammable Liquids - B2  
 Other Toxic Effects - D2A  
 Other Toxic Effects - D2B

**Other hazards**

WHMIS • In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

**Section 3 - Composition/Information on Ingredients****Substances**

• Material does not meet the criteria of a substance.

**Mixtures**

Composition		
Chemical Name	Identifiers	%
Styrene	CAS:100-42-5	30%
Methyl Methacrylate	CAS:80-62-6	5%
Vinyl Toluene	CAS:25013-15-4	3%
Proprietary	Proprietary	0% TO 2%
Cobalt 2-Ethylhexanoate	CAS:136-52-7	0.1% TO 0.3%

**Section 4: First-Aid Measures****Description of first aid measures**

**Inhalation** • Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. Do not use mouth-to-mouth method if victim inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention immediately.

**Skin** • In case of contact with substance, immediately flush skin with running water for at least 20 minutes. Remove and isolate contaminated clothing. Wash skin with soap and water. If irritation develops and persists, get medical attention.

- Eye** • In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.
- Ingestion** • Do NOT induce vomiting. Do not use mouth-to-mouth method if victim ingested the substance. Obtain medical attention immediately if ingested.

### Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

### Indication of any immediate medical attention and special treatment needed

- Notes to Physician** • All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

## Section 5: Fire-Fighting Measures

### Extinguishing media

- Suitable Extinguishing Media** • Water fog or fine spray, carbon dioxide fire extinguishers, dry chemical fire extinguishers, foam.  
General purpose synthetic foams (including AFFF type) or protein foams are preferred if available. Alcohol resistant foams (ATC type) may function.

- Unsuitable Extinguishing Media** • Do not use direct water stream.

### Special hazards arising from the substance or mixture

- Unusual Fire and Explosion Hazards** • HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Containers may explode when heated. Many liquids are lighter than water. Vapors may form explosive mixtures with air. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to source of ignition and flash back. Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

- Hazardous Combustion Products** • The original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to phenolic compounds, carbon monoxide, carbon dioxide.

### Advice for firefighters

- Structural firefighters' protective clothing will only provide limited protection. Wear positive pressure self-contained breathing apparatus (SCBA). Move containers from fire area if you can do it without risk. LARGE FIRES: Cool containers with flooding quantities of water until well after fire is out.

## Section 6 - Accidental Release Measures

### Personal precautions, protective equipment and emergency procedures

- Personal Precautions** • Ventilate enclosed areas. CAUTION: Victim may be a source of contamination. Do not walk through spilled material. Wear appropriate personal protective equipment, avoid direct contact. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

- Emergency Procedures** • As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. LARGE SPILL: Consider initial downwind evacuation for at least 300 meters (1000 feet) ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unauthorized personnel away. Stay upwind. Keep out of low areas.

### Environmental precautions

- Prevent entry into waterways, sewers, basements or confined areas.

## Methods and material for containment and cleaning up

- Containment/Clean-up Measures**
- Stop leak if you can do it without risk.
  - Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
  - Use clean non-sparking tools to collect absorbed material.
  - A vapor suppressing foam may be used to reduce vapors.
  - All equipment used when handling the product must be grounded.
  - LARGE SPILLS: Dike far ahead of liquid spill for later disposal.
  - LARGE SPILLS: Water spray may reduce vapor; but may not prevent ignition in closed spaces.

## Section 7 - Handling and Storage

### Precautions for safe handling

- Handling**
- Keep away from heat, sparks, and flame. Do not use sparking tools. Take precautionary measures against static charges. All equipment used when handling the product must be grounded. Wear appropriate personal protective equipment, avoid direct contact. Do not breathe mist, vapours and/or spray. Avoid contact with skin, eyes, and clothing. Avoid direct contact of MEKP catalyst with accelerator. If an accelerator such as cobalt drier is to be added, mix this accelerator with base material before adding catalyst. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.

### Conditions for safe storage, including any incompatibilities

- Storage**
- Store in a tightly closed container. Store in a cool/low-temperature, well-ventilated place.

## Section 8 - Exposure Controls/Personal Protection

### Control parameters

	Result	Exposure Limits/Guidelines		
		ACGIH	NIOSH	OSHA
Vinyl Toluene (25013-15-4)	TWAs	50 ppm TWA	100 ppm TWA; 480 mg/m <sup>3</sup> TWA	100 ppm TWA; 480 mg/m <sup>3</sup> TWA
	STELs	100 ppm STEL	Not established	Not established
Methyl Methacrylate (80-62-6)	TWAs	50 ppm TWA	100 ppm TWA; 410 mg/m <sup>3</sup> TWA	100 ppm TWA; 410 mg/m <sup>3</sup> TWA
	STELs	100 ppm STEL	Not established	Not established
Styrene (100-42-5)	Ceilings	Not established	Not established	200 ppm Ceiling
	TWAs	20 ppm TWA	50 ppm TWA; 215 mg/m <sup>3</sup> TWA	100 ppm TWA
	STELs	40 ppm STEL	100 ppm STEL; 425 mg/m <sup>3</sup> STEL	Not established

### Exposure controls

- Engineering Measures/Controls**
- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof electrical/ventilating/lighting/equipment.

### Personal Protective Equipment

- Respiratory**
- In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced.
- Eye/Face**
- Wear safety goggles.
- Skin/Body**
- Wear appropriate gloves. Wear long sleeves and/or protective coveralls.
- Environmental Exposure Controls**
- Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways. Follow best practice for site management and disposal of waste.

**Key to abbreviations**

ACGIH = American Conference of Governmental Industrial Hygiene

NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15-minute exposures

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

**Section 9 - Physical and Chemical Properties****Information on Physical and Chemical Properties**

<b>Material Description</b>			
Physical Form	Liquid	Appearance/Description	A green liquid with a pungent odor.
Color	Green	Odor	Pungent
Odor Threshold	No data available		
<b>General Properties</b>			
Boiling Point	293 °F(145 °C)	Melting Point/Freezing Point	-23.8 °F(-31 °C)
Decomposition Temperature	No data available	pH	No data available
Specific Gravity/Relative Density	1.05 to 1.1 Water=1	Water Solubility	Slightly Soluble 0.1 to 1 %
Viscosity	No data available		
<b>Volatility</b>			
Vapor Pressure	5 mmHg (torr) @ 20 °F(-6.6667 °C)	Vapor Density	3.6 Air=1
Evaporation Rate	No data available	Volatiles (Wt.)	36 to 39 %
Volatiles (Vol.)	36 to 39 %		
<b>Flammability</b>			
Flash Point	31 °C(87.8 °F)	UEL	No data available
LEL	No data available	Autoignition	No data available
Flammability (solid, gas)	No data available		
<b>Environmental</b>			
Octanol/Water Partition coefficient	No data available		

**Section 10: Stability and Reactivity****Reactivity**

- No dangerous reaction known under conditions of normal use.

**Chemical stability**

- Stable under normal temperatures and pressures.

**Possibility of hazardous reactions**

- Hazardous polymerization will not occur.

**Conditions to avoid**

- Keep away from heat, sparks and flame.

**Incompatible materials**

- Oxidizing Materials.

**Hazardous decomposition products**

- Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**Section 11 - Toxicological Information****Information on toxicological effects**

Components		
Styrene (30%)	100-42-5	<p><b>Acute Toxicity:</b> Ingestion/Oral-Rat LD50 • 2650 mg/kg; <i>Behavioral:Somnolence (general depressed activity); Liver:Other changes;</i> Inhalation-Rat LC50 • 11800 mg/m<sup>3</sup> 4 Hour(s); Inhalation-Human TClO • 376 ppm 1 Hour(s); <i>Peripheral Nerve and Sensation:Flaccid paralysis without anesthesia (usually neuromuscular blockage); Behavioral:Changes in motor activity (specific assay); Irritation:</i> Eye-Rabbit • 100 mg 24 Hour(s) • Moderate irritation; Skin-Rabbit • 100 % • Moderate irritation; <b>Multi-dose Toxicity:</b> Inhalation-Mouse TClO • 500 ppm 6 Hour(s) 22 Day(s)-Intermittent; <i>Liver:Hepatitis (hepatocellular necrosis), diffuse; Blood:Changes in serum composition (e.g., TP, bilirubin cholesterol); Biochemical:Enzyme inhibition, induction, or change in blood or tissue levels:Other transferases;</i> Inhalation-Mouse TClO • 250 ppm 6 Hour(s) 14 Day(s)-Intermittent; <i>Liver:Hepatitis (hepatocellular necrosis), zonal; Liver:Changes in liver weight; Related to Chronic Data:Death in the Other Multiple Dose data type field;</i> Inhalation-Mouse TClO • 500 ppm 90 Day(s)-Intermittent; <i>Lungs, Thorax, or Respiration:Structural or functional change in trachea or bronchi; Liver:Hepatitis (hepatocellular necrosis), zonal; Related to Chronic Data:Death in the Other Multiple Dose data type field;</i> Inhalation-Rat TClO • 600 ppm 4 Week(s)-Intermittent; <i>Sense Organs and Special Senses:Ear:Change in acuity; Sense Organs and Special Senses:Ear:Changes in cochlear structure or function;</i> <b>Mutagen:</b> Sister chromatid exchange • Inhalation-Human • 1204 mg/m<sup>3</sup> 5 Year(s)-Intermittent; DNA adduct • Inhalation-Mouse • 1500 µg/L 21 Day(s)-Intermittent; Sister chromatid exchange • Inhalation-Mouse • 125 ppm 4 Day(s)-Intermittent; Cytogenetic analysis • Inhalation-Rat • 300 ppm 8 Week(s)-Intermittent; <b>Reproductive:</b> Inhalation-Rat TClO • 1500 µg/m<sup>3</sup> 24 Hour(s)(1-22D preg); <i>Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus); Reproductive Effects:Effects on Embryo or Fetus:Fetal death;</i> Inhalation-Rat TClO • 5 mg/m<sup>3</sup> 24 Hour(s)(1-22D preg); <i>Reproductive Effects:Effects on Newborn:Stillbirth; Reproductive Effects:Effects on Newborn:Weaning or lactation index;</i> <b>Tumorigen / Carcinogen:</b> Inhalation-Mouse TClO • 20 ppm 6 Hour(s) 98 Week(s)-Intermittent; <i>Tumorigenic:Neoplastic by RTECS criteria; Lungs, Thorax, or Respiration:Tumors;</i> Inhalation-Mouse TClO • 160 ppm 6 Hour(s) 98 Week(s)-Intermittent; <i>Tumorigenic:Carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration:Tumors;</i> Inhalation-Rat TClO • 100 ppm 4 Hour(s) 5 Day(s)-Intermittent; <i>Tumorigenic:Carcinogenic by RTECS criteria; Skin and Appendages:Other:Tumors; Blood:Leukemia</i></p>
Methyl Methacrylate (5%)	80-62-6	<p><b>Acute Toxicity:</b> Ingestion/Oral-Rabbit LD50 • 8700 mg/kg; Inhalation-Rat LC50 • 78000 mg/m<sup>3</sup> 4 Hour(s); <b>Irritation:</b> Eye-Rabbit • 150 mg; Skin-Rabbit • 10 g-Open; <b>Reproductive:</b> Inhalation-Rat TClO • 500 mg/m<sup>3</sup> (122D pre); <i>Reproductive Effects:Specific Developmental Abnormalities:Other developmental abnormalities</i></p>
Vinyl Toluene (3%)	25013-15-4	<p><b>Acute Toxicity:</b> Ingestion/Oral-Rat LD50 • 2255 mg/kg; <i>Sense Organs and Special Senses:Eye:Lacrimation; Behavioral:Somnolence (general depressed activity); Skin and Appendages:Other:Hair;</i> <b>Irritation:</b> Eye-Rabbit • 90 mg • Mild irritation; Skin-Rabbit • 100 % • Moderate irritation</p>
Cobalt 2-Ethylhexanoate (0.1% TO 0.3%)	136-52-7	<p><b>Acute Toxicity:</b> Ingestion/Oral-Rat LD50 • 1.22 g/kg; <i>Behavioral:Ataxia; Behavioral:Coma;</i> Inhalation-Rat LC50 • &gt;10000 mg/m<sup>3</sup> 1 Hour(s); Skin-Rabbit LD50 • &gt;5 g/kg; <i>Skin and Appendages:After topical exposure:Primary irritation</i></p>

GHS Properties	Classification
Acute toxicity	OSHA HCS 2012•Acute Toxicity - Inhalation 4 - ATEmix (Inhl, Vapor) =15.7 mg/L 4H
Skin corrosion/Irritation	OSHA HCS 2012•Skin Irritation 2
Serious eye damage/Irritation	OSHA HCS 2012•Eye Irritation 2
Skin sensitization	OSHA HCS 2012•Skin Sensitizer 1B
Respiratory sensitization	OSHA HCS 2012•Respiratory Sensitizer 1B
Aspiration Hazard	OSHA HCS 2012•Aspiration 1
Carcinogenicity	OSHA HCS 2012•Carcinogenicity 2
Germ Cell Mutagenicity	OSHA HCS 2012•No data available
Toxicity for Reproduction	OSHA HCS 2012•Toxic to Reproduction 2
STOT-SE	OSHA HCS 2012•Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation
STOT-RE	OSHA HCS 2012•Specific Target Organ Toxicity Repeated Exposure 1

## Potential Health Effects

### Inhalation

#### Acute

- Harmful if inhaled. May cause respiratory irritation.

**(Immediate)**

**Chronic (Delayed)** • May cause allergy or asthma symptoms or breathing difficulties if inhaled. Repeated and prolonged exposure Causes damage to the auditory system.

**Skin**

**Acute (Immediate)** • Causes skin irritation. May cause skin sensitization. Symptoms include redness, and skin rash.

**Chronic (Delayed)** • No data available

**Eye**

**Acute (Immediate)** • Causes serious eye irritation.

**Chronic (Delayed)** • No data available

**Ingestion**

**Acute (Immediate)** • Material may be aspirated into lungs during ingestion and/or subsequent vomiting. Aspiration of this material will cause severe lung injury, chemical pneumonitis, pulmonary edema or death.

**Chronic (Delayed)** • No data available

**Carcinogenic Effects** • Repeated and prolonged exposure may cause cancer.

<b>Carcinogenic Effects</b>			
	<b>CAS</b>	<b>IARC</b>	<b>NTP</b>
Styrene	100-42-5	Group 2B-Possible Carcinogen	Reasonably Anticipated to be Human Carcinogen

**Reproductive Effects** • Repeated and prolonged exposure may cause reproductive effects.

**Key to abbreviations**

LC = Lethal Concentration

LD = Lethal Dose

TC = Toxic Concentration

TD = Toxic Dose

## Section 12 - Ecological Information

**Toxicity**

• Non-mandatory section - information about this substance not compiled for this reason.

**Persistence and degradability**

• Non-mandatory section - information about this substance not compiled for this reason.

**Bioaccumulative potential**

• Non-mandatory section - information about this substance not compiled for this reason.

**Mobility in Soil**

• Non-mandatory section - information about this substance not compiled for this reason.

**Other adverse effects**

• Non-mandatory section - information about this substance not compiled for this reason.

## Section 13 - Disposal Considerations

**Waste treatment methods**



- Product waste** • Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.
- Packaging waste** • Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

### Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class(es)	Packing group	Environmental hazards
DOT	UN1866	Resin solution	3	III	NDA
TDG	UN1866	RESIN SOLUTION	3	III	NDA

**Special precautions for user** • None specified.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** • No data available

### Section 15 - Regulatory Information

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

**SARA Hazard Classifications** • Fire, Acute, Chronic

Inventory				
Component	CAS	Canada DSL	Canada NDSL	TSCA
Styrene	100-42-5	Yes	No	Yes
Cobalt 2-Ethylhexanoate	136-52-7	Yes	No	Yes
Methyl Methacrylate	80-62-6	Yes	No	Yes
Vinyl Toluene	25013-15-4	Yes	No	Yes

#### Canada

##### Labor

###### Canada - WHMIS - Classifications of Substances

•Vinyl Toluene	25013-15-4	B3, D2B
•Cobalt 2-Ethylhexanoate	136-52-7	Not Listed
•Methyl Methacrylate	80-62-6	B2, D2B
•Styrene	100-42-5	B2, D2A

###### Canada - WHMIS - Ingredient Disclosure List

•Vinyl Toluene	25013-15-4	1 %
•Cobalt 2-Ethylhexanoate	136-52-7	Not Listed
•Methyl Methacrylate	80-62-6	1 %
•Styrene	100-42-5	0.1 %

##### Environment

###### Canada - CEPA - Priority Substances List

•Vinyl Toluene	25013-15-4	Not Listed
•Cobalt 2-Ethylhexanoate	136-52-7	Not Listed
•Methyl Methacrylate	80-62-6	Priority Substance List 1 (substance not considered toxic)
•Styrene	100-42-5	Priority Substance List 1 (substance not considered toxic)

#### United States

##### Labor

**U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals**

•Vinyl Toluene	25013-15-4	Not Listed
•Cobalt 2-Ethylhexanoate	136-52-7	Not Listed
•Methyl Methacrylate	80-62-6	Not Listed
•Styrene	100-42-5	Not Listed
<b>U.S. - OSHA - Specifically Regulated Chemicals</b>		
•Vinyl Toluene	25013-15-4	Not Listed
•Cobalt 2-Ethylhexanoate	136-52-7	Not Listed
•Methyl Methacrylate	80-62-6	Not Listed
•Styrene	100-42-5	Not Listed

## Environment

### U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

•Vinyl Toluene	25013-15-4	Not Listed
•Cobalt 2-Ethylhexanoate	136-52-7	Not Listed
•Methyl Methacrylate	80-62-6	
•Styrene	100-42-5	

### U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

•Vinyl Toluene	25013-15-4	Not Listed
•Cobalt 2-Ethylhexanoate	136-52-7	Not Listed
•Methyl Methacrylate	80-62-6	1000 lb final RQ; 454 kg final RQ
•Styrene	100-42-5	1000 lb final RQ; 454 kg final RQ

### U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities

•Vinyl Toluene	25013-15-4	Not Listed
•Cobalt 2-Ethylhexanoate	136-52-7	Not Listed
•Methyl Methacrylate	80-62-6	Not Listed
•Styrene	100-42-5	Not Listed

### U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

•Vinyl Toluene	25013-15-4	Not Listed
•Cobalt 2-Ethylhexanoate	136-52-7	Not Listed
•Methyl Methacrylate	80-62-6	Not Listed
•Styrene	100-42-5	Not Listed

### U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

•Vinyl Toluene	25013-15-4	Not Listed
•Cobalt 2-Ethylhexanoate	136-52-7	Not Listed
•Methyl Methacrylate	80-62-6	Not Listed
•Styrene	100-42-5	Not Listed

### U.S. - CERCLA/SARA - Section 313 - Emission Reporting

•Vinyl Toluene	25013-15-4	Not Listed
•Cobalt 2-Ethylhexanoate	136-52-7	Not Listed
•Methyl Methacrylate	80-62-6	1.0 % de minimis concentration
•Styrene	100-42-5	0.1 % de minimis concentration

### U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

•Vinyl Toluene	25013-15-4	Not Listed
•Cobalt 2-Ethylhexanoate	136-52-7	Not Listed
•Methyl Methacrylate	80-62-6	Not Listed
•Styrene	100-42-5	Not Listed

## United States - California

### Environment

#### U.S. - California - Proposition 65 - Carcinogens List

•Vinyl Toluene	25013-15-4	Not Listed
•Cobalt 2-Ethylhexanoate	136-52-7	Not Listed
•Methyl Methacrylate	80-62-6	Not Listed
•Styrene	100-42-5	Not Listed

#### U.S. - California - Proposition 65 - Developmental Toxicity

•Vinyl Toluene	25013-15-4	Not Listed
•Cobalt 2-Ethylhexanoate	136-52-7	Not Listed
•Methyl Methacrylate	80-62-6	Not Listed
•Styrene	100-42-5	Not Listed

#### U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

•Vinyl Toluene	25013-15-4	Not Listed
----------------	------------	------------

•Cobalt 2-Ethylhexanoate	136-52-7	Not Listed
•Methyl Methacrylate	80-62-6	Not Listed
•Styrene	100-42-5	Not Listed
<b>U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)</b>		
•Vinyl Toluene	25013-15-4	Not Listed
•Cobalt 2-Ethylhexanoate	136-52-7	Not Listed
•Methyl Methacrylate	80-62-6	Not Listed
•Styrene	100-42-5	Not Listed
<b>U.S. - California - Proposition 65 - Reproductive Toxicity - Female</b>		
•Vinyl Toluene	25013-15-4	Not Listed
•Cobalt 2-Ethylhexanoate	136-52-7	Not Listed
•Methyl Methacrylate	80-62-6	Not Listed
•Styrene	100-42-5	Not Listed
<b>U.S. - California - Proposition 65 - Reproductive Toxicity - Male</b>		
•Vinyl Toluene	25013-15-4	Not Listed
•Cobalt 2-Ethylhexanoate	136-52-7	Not Listed
•Methyl Methacrylate	80-62-6	Not Listed
•Styrene	100-42-5	Not Listed

## Section 16 - Other Information

- Last Revision Date** • 07/January/2016
- Preparation Date** • 07/January/2016
- Disclaimer/Statement of Liability** • The information herein is given in good faith, but no warranty, express or implied, is made. Consult Polycry Corporation for further information. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use, or disposal of the product. This SDS was prepared and is to be used only for these products. If the product is used as a component in another product, this SDS information may not be applicable.

**Key to abbreviations**

NDA = No Data Available